



SBNH-1D65A

Andrew® dual band Antenna, 698–896 and 1695–2360 MHz, 65° horizontal beamwidth, internal RETs.

- Interleaved dipole technology providing for attractive, low wind load mechanical package

Electrical Specifications

Frequency Band, MHz	698–806	790–896	1695–1880	1850–1990	1920–2200	2300–2360
Gain, dBi	13.3	13.3	16.4	16.6	17.2	17.3
Beamwidth, Horizontal, degrees	68	62	70	64	61	60
Beamwidth, Vertical, degrees	17.6	16.1	7.0	6.5	6.1	5.4
Beam Tilt, degrees	0–18	0–18	0–10	0–10	0–10	0–10
USLS (First Lobe), dB	16	15	15	14	13	12
Front-to-Back Ratio at 180°, dB	28	26	33	32	27	30
Isolation, dB	25	25	25	25	25	25
Isolation, Intersystem, dB	30	30	30	30	30	30
VSWR Return Loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153	-153	-153
Input Power per Port, maximum, watts	350	350	350	350	350	300
Polarization	±45°	±45°	±45°	±45°	±45°	±45°
Impedance	50 ohm	50 ohm	50 ohm	50 ohm	50 ohm	50 ohm

Electrical Specifications, BASTA*

Frequency Band, MHz	698–806	790–896	1695–1880	1850–1990	1920–2200	2300–2360
Gain by all Beam Tilts, average, dBi	13.1	12.9	16.0	16.4	16.6	17.1
Gain by all Beam Tilts Tolerance, dB	±0.5	±0.6	±0.5	±0.3	±0.6	±0.4
Gain by Beam Tilt, average, dBi	0° 13.4	0° 13.2	0° 15.9	0° 16.1	0° 16.3	0° 17.0
	9° 13.2	9° 13.0	5° 16.1	5° 16.5	5° 16.7	5° 17.2
	18° 12.7	18° 12.5	10° 15.9	10° 16.4	10° 16.6	10° 16.7
Beamwidth, Horizontal Tolerance, degrees	±2.6	±5	±3.4	±3.6	±7.7	±4.1
Beamwidth, Vertical Tolerance, degrees	±1.4	±1.2	±0.3	±0.3	±0.5	±0.2
USLS, beampeak to 20° above beampeak, dB	16	16	13	15	15	13
Front-to-Back Total Power at 180° ± 30°, dB	24	22	26	26	23	24
CPR at Boresight, dB	21	17	20	26	22	21
CPR at Sector, dB	9	5	11	9	4	5

* CommScope® supports NGMN recommendations on Base Station Antenna Standards (BASTA). To learn more about the benefits of BASTA, [download the whitepaper Time to Raise the Bar on BSAs.](#)

General Specifications

Antenna Brand	Andrew®
Antenna Type	DualPol® multiband
Band	Multiband
Brand	DualPol®
Operating Frequency Band	1695 – 2360 MHz 698 – 896 MHz
Performance Note	Outdoor usage

Mechanical Specifications

Color	Light gray
-------	------------

SBNH-1D65A

Lightning Protection	dc Ground
Radiator Material	Copper Low loss circuit board
Radome Material	Fiberglass, UV resistant
Reflector Material	Aluminum
RF Connector Interface	7-16 DIN Female
RF Connector Location	Bottom
RF Connector Quantity, total	4
Wind Loading, maximum	445.0 N @ 150 km/h 100.0 lbf @ 150 km/h
Wind Speed, maximum	241 km/h 150 mph

Dimensions

Depth	180.5 mm 7.1 in
Length	1412.0 mm 55.6 in
Width	301.0 mm 11.9 in
Net Weight	13.6 kg 30.0 lb

Remote Electrical Tilt (RET) Information

Input Voltage	10–30 Vdc
Power Consumption, idle state, maximum	2.0 W
Power Consumption, normal conditions, maximum	13.0 W
Protocol	3GPP/AISG 2.0 (Multi-RET)
RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	1 female 1 male

Packed Dimensions

Depth	299.0 mm 11.8 in
Length	1532.0 mm 60.3 in
Width	409.0 mm 16.1 in
Shipping Weight	24.5 kg 54.0 lb

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant by Exemption
China RoHS SJ/T 11364-2006	Above Maximum Concentration Value (MCV)
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



Included Products

BSAMNT-1 — Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

SBNH-1D65A

* **Footnotes**

Performance Note	Severe environmental conditions may degrade optimum performance
------------------	---